

10.4" inch Touch Monitor (POS-styler)

Products application :

- POS Terminal
- Industrial PC
- Kiosk
- Gaming
- Medical apparatus
- Personal computer
- Mobile GPS
- Office automation
- Security system of the house
- Car-mounted amusement
- Military equipment
- Communicate



Black : R01V



White : RW01V



10.4" inch Touch Monitor (POS-styler)

Display Specifications :

Active Area	211 × 158 mm
Pixel Pitch	0.20625 × 0.20625 mm
Brightness	400 cd/m ²
Contrast Ratio	500 : 1
Resolution	1024 x 768 (XGA)
Viewing Angle	L/R 140° ; U/D 120°
Response Time	25 ms (Tr + Tf)
Display Colors	262K
Display Modes	640×480 ; 800×600 ; 1024×768
Signal input	15 Pin D_Sub ; Mini-Audio in ; DVI
Mini-Audio out	1W (8Ω) × 1
OSD Keyboard	⊙ Menu/Select ⊙ - ⊙ + ⊙ Auto/Exit ⊙ Power
Power Source	DC 12V ; ≤9w ; Standby ≤1w
Power Consumption	
Storage \ Operation	-30~80°C ; -20~70°C
VESA	75×75 or 100×100 mm
Casing Colors	Black or White
Casing Size \ Weight	254.8 × 196.9 × 45.5 mm ; 3.5kg (W×H×D)
Carton \ gross weight	385 × 365 × 185 mm ; 4.9kg (W×H×D)



Touch Feature :

Input Method	Finger, gloved hand, or stylus activation
Activation Force	≥50g
Linearity	≤1.5%
Surface	≥3H
Life Time	≤35,000,000
Application	Writing and Signature Capture Capability
PC Link	USB or RS232

Software Feature :

Calibration	Fast full oriental 4 points position
Compensation	Edge compensation. Accuracy 25 points linearity compensation
Draw Test	Position and linearity verification
Controller	Support multiple controllers
Languages	English \ Simple Chinese \ Traditional Chinese \ Japanese \ French \ German \ Spanish \ Korean \ Arabic \ Czech \ Danish \ Dutch \ Greek \ Hungarian \ Italian \ Norwegian \ Russian \ Polish \ Portuguese \ Slovenian \ Swedish \ Thai \ Turkish
Mouse Emulator	Right / left button emulation. Auto Right / left Click (PDA function)
Touch Style	Drawing a Mode \ button a Mode \ Touch Off/ on Switch
Double Click	Configurable double click speed \ Configurable double click area
Sound Modes	No sound \ Touch down \ Touch up
COM Port Support	COM1 ~ COM255 for Windows and Linux COM1 ~ COM8 for MS- DOS
Display Support	display rotation \ Support multiple monitors
Support O.S	All Windows-32 bit O.S Windows7-8-10 ; XP-64 bit O.S MS-DOS ; All Linux ; MAC

Order information :

AIM-TM5R104-R01V :	【VGA/AUDIO/DVI/USB-Touch/Black】	AIM-TM5R104-R02V :	【VGA/AUDIO/DVI/RS232-Touch/Black】
AIM-TM5R104-RW01V :	【VGA/AUDIO/DVI/USB-Touch/White】	AIM-TM5R104-RW02V :	【VGA/AUDIO/DVI/RS232-Touch/White】
Accessory	VGA Cable/AC90~260V Adapter/Power Cable/Audio Cable/USB or RS232 Cable/Touch Pen/Cleaning wipes/		
	Driver Disk ※DVI Cable(Optional)		



3 Year Warranty
LCD Panel 1 Year

