



10.4" inch Touch Monitor (Infrared Ray Multi-Touch)

Products application :

- POS Terminal
- Industrial PC
- Kiosk
- Gaming
- Medical apparatus
- Personal computer
- Mobile GPS
- Office automation
- Security system of the house
- Car-mounted amusement
- Military equipment
- Communicate



10.4" inch Touch Monitor (Infrared Ray Multi-Touch)

Display Specifications :

| | |
|---------------------|---|
| Active Area | 211 × 158 mm |
| Pixel Pitch | 0.20625 × 0.20625 mm |
| Brightness | 400 cd/m ² |
| Contrast Ratio | 500 : 1 |
| Resolution | 1024 × 768 (XGA) |
| Viewing Angle | L/R 140° ; U/D120° |
| Response Time | 25 ms (Tr + Tf) |
| Display Colors | 262K |
| Display Modes | 640×480 ; 800×600 ; 1024×768 |
| Signal input | 15 Pin D_Sub ; Mini-Audio in ; DVI |
| Mini-Audio out | 1W (8Ω) × 1 |
| OSD Keyboard | ⊙ Menu/Select ⊙ - ⊙ + ⊙ Auto/Exit ⊙ Power |
| Power Source | DC 12V ; ≤9w ; Standby ≤1w |
| Power Consumption | |
| Storage Operation | -30~80°C ; -20~70°C |
| VESA | 75×75 or 100×100 mm |
| Casing Colors | Black |
| Casing Size Weight | 257 × 204 × 48 mm ; 2.9kg (W×H×D) |
| Carton gross weight | 385 × 365 × 185 mm ; 4.7kg (W×H×D) |



Touch Feature :

| | |
|--------------|--|
| Input Method | It detects anything that blocks lights |
| Linearity | ≤2.5mm |
| Surface | ≥7H |
| Life Time | Unlimited |
| Application | Writing and Signature Capture Capability |
| PC Link | USB |

Software Feature :

| | |
|----------------------------|--|
| Calibration | 4 points or 16 points or 25 points |
| Draw Test | Position and linearity verification |
| Controller | Support multiple controllers |
| Languages | English 、 Simple Chinese 、 Traditional Chinese 、 Japanese 、 German |
| Mouse Emulator | Right / left button emulation. Auto Right / left Click (PDA function) |
| Touch Style | Drawing a Mode 、 button a Mode 、 Hide cursor |
| Double Click | Configurable double click speed 、 Configurable double click area |
| Sound Modes | No sound 、 Touch down 、 Touch up |
| Display Support | display rotation 、 Support multiple monitors |
| Division Pattern Settings: | Support two halves and four parts with touch function, you can also create your own division patterns. |
| Edge compensation | Support edge compensation and you can also add your own numbers for it. |
| Support O.S | All Windows-32 bit O.S Windows7-8-10 ; XP-64 bit O.S Android ; AII Linux ; MAC |



Order Information :

AIM-TMIR104-R01V :
Accessory

【VGA/DVI/AUDIO/USB-TOUCH】

VGA Cable/Audio Cable/Power Cable/AC90~260V Adapter/USB Cable/Cleaning wipes/Driver Disk

※DVI Cable(Optional)



3 Year Warranty
LCD Panel 1 Year

