

## 19" inch Touch Monitor (POS-styler)

### Products application :

- POS Terminal
- Industrial PC
- Kiosk
- Gaming
- Medical apparatus
- Personal computer
- Mobile GPS
- Office automation
- Security system of the house
- Car-mounted amusement
- Military equipment
- Communicate



**Black : V01**





**White : VW01**



## 19" inch Touch Monitor (POS-styler)

### Display Specifications :

Active Area	376 × 301 mm
Pixel Pitch	0.294 × 0.294 mm
Brightness	250 cd/m <sup>2</sup>
Contrast Ratio	1000 : 1
Resolution	1280 x 1024 ( SXGA )
Viewing Angle	L/R 170° ; U/D 160°
Response Time	5 ms ( Tr + Tf )
Display Colors	16.7M
Display Modes	640×480 ; 800×600 ; 1024×768 ; 1280×1024
Signal input	15 Pin D_Sub ; Mini-Audio in
Mini-Audio out	1W ( 8Ω ) × 1
OSD Keyboard	⊙Power ⊙Auto adjust ⊕ ⊖ ⊙Menu
Power Source	DC 12V ; ≤16w ; Standby ≤1w
Power Consumption	
Storage · Operation	-20~60°C ; 0~50°C
VESA	75×75 mm
Casing Colors	Black or White
Casing Size · Weight	421.4 × 350.5 × 48.1 mm ; 6.2kg ( W×H×D )
Carton · gross weight	490 × 500 × 155 mm ; 7.6kg ( W×H×D )



### Touch Feature :

Input Method	Finger, gloved hand, or stylus activation
Activation Force	≥50g
Linearity	≤1.5%
Surface	≥3H
Life Time	≤35,000,000
Application	Writing and Signature Capture Capability
PC Link	USB or RS232

### Software Feature :

Calibration	Fast full oriental 4 points position
Compensation	Edge compensation. Accuracy 25 points linearity compensation
Draw Test	Position and linearity verification
Controller	Support multiple controllers
Languages	English · Simple Chinese · Traditional Chinese · Japanese · French · German · Spanish · Korean · Arabic · Czech · Danish · Dutch · Greek · Hungarian · Italian · Norwegian · Russian · Polish · Portuguese · Slovenian · Swedish · Thai · Turkish
Mouse Emulator	Right / left button emulation. Auto Right / left Click ( PDA function )
Touch Style	Drawing a Mode · button a Mode · Touch Off/ on Switch
Double Click	Configurable double click speed · Configurable double click area
Sound Modes	No sound · Touch down · Touch up
COM Port Support	COM1 ~ COM255 for Windows and Linux COM1 ~ COM8 for MS- DOS
Display Support	display rotation · Support multiple monitors
Support O.S	All Windows-32 bit O.S Windows7-8-10 ; XP-64 bit O.S MS-DOS : All Linux : MAC

### Order information :

AIM-TM5R190-V01 :	【VGA/AUDIO/USB-TOUCH/Black】	AIM-TM5R190-V02 :	【VGA/AUDIO/RS232-TOUCH/Black】
AIM-TM5R190-VW01 :	【VGA/AUDIO/USB-TOUCH/White】	AIM-TM5R190-VW02 :	【VGA/AUDIO/RS232-TOUCH/White】
AIM-TM5R190-V05 :	【VGA/AUDIO/DVI/USB-Touch/Black】	AIM-TM5R190-V06 :	【VGA/AUDIO/DVI/RS232-Touch/Black】
AIM-TM5R190-VW05 :	【VGA/AUDIO/DVI/USB-Touch/White】	AIM-TM5R190-VW06 :	【VGA/AUDIO/DVI/RS232-Touch/White】
Accessory	VGA Cable/AC90~260V Adapter/Power Cable/Audio Cable/USB or RS232 Cable/Touch Pen/Cleaning wipes/Driver Disk ※DVI Cable		



**3 Year Warranty**  
LCD Panel 1 Year

