

Note :

- Pin 1 : X1 (Left)
- Pin 2 : Y1 (Bottom)
- Pin 3 : X2 (Right)
- Pin 4 : Y2 (Top)

Pin Pitch : 1.0 mm


ITO Glass : 1.1 mm

Total Thickness : 1.4±0.1 mm

Faceplate Surface : Anti -glare coating

**Active Area Inside Active**

**Active Area Outside Non-Active**

|  |                   |                       |               |                     |                 |                         |
|--|-------------------|-----------------------|---------------|---------------------|-----------------|-------------------------|
| 瞄準科技有限公司<br>AIM TOUCH TECHNOLOGY CO.,LTD.  | DATE : 2007/03/07 | Part Number           | ITO Film Type | Glass Type          | Glass Thickness | Finished Part Thickness |
|  | MODEL :           | AIM-4R-0360-M03-G0N   | ANTI GLARE    | General             | 0.7mm           | 1.0mm±0.1               |
| <br>WWW.AIMTOUCH.COM.TW | AIM-4R-0360-M03   | AIM-4R-0360-M03-G07SN | ANTI GLARE    | chemical strengthen | 0.7mm           | 1.0mm±0.1               |
|  |                   | AIM-4R-0360-M03-G1N   | ANTI GLARE    | General             | 1.1mm           | 1.4mm±0.1               |

NOTE : All indications are the millimeters.