




**10.4" inch Touch Monitor (Pure Flat Projected capacitive Multi-Touch)**

**Products application :**

- POS Terminal
- Industrial PC
- Kiosk
- Gaming
- Medical apparatus
- Personal computer
- Mobile GPS
- Office automation
- Security system of the house
- Car-mounted amusement
- Military equipment
- Communicate



## 10.4" inch Touch Monitor (Pure Flat Projected capacitive Multi-Touch)

### Display Specifications :

Active Area	210 × 157 mm
Pixel Pitch	0.0685 × 0.2055 mm
Brightness	350 cd/m <sup>2</sup>
Contrast Ratio	1000 : 1
Resolution	1024 × 768 ( XGA )
Viewing Angle	L/R 178° ; U/D 178°
Response Time	25 ms ( Tr + Tf )
Display Colors	16.2 M
Display Modes	640×480 ; 800×600 ; 1024 × 768
Signal input	VGA ; Audio ; DVI
Mini-Audio out	1W ( 8Ω ) × 1
OSD Keyboard	⊙Menu/Select ⊖ ⊕ ⊙Auto/Exit ⊙Power
Power Source	DC 12V ; ≤ 10w ; Standby ≤ 1w
Power Consumption	
Storage · Operation	-20~70°C ; -20~70°C
VESA	75×75 or 100×100 mm
Casing Colors	Black
Casing Size · Weight	280.6 × 187.6 × 46 mm ; 1.7kg ( W×H×D )
Carton · gross weight	385 × 365 × 185 mm ; 3.3kg ( W×H×D )



### Touch Feature :

Input Method	Capacitive stylus, Finger
Linearity	≤ 2.5mm
Life Time	Unlimited
Surface	≥ 7H
Application	Writing and Signature Capture Capability
PC Link	USB or RS232(Single-Touch)

### Software Feature :

Draw Test	Position and linearity verification
Controller	Support multiple controllers
Languages	English · Simple Chinese · Traditional Chinese · Japanese · French · German · Spanish · Korean · Arabic · Czech · Danish · Dutch · Greek · Hungarian · Italian · Norwegian · Russian · Polish · Portuguese · Slovenian · Swedish · Thai · Turkish
Mouse Emulator	Right / left button emulation. Auto Right / left Click ( PDA function )
Touch Style	Drawing a Mode · button a Mode · Touch Off/ on Switch
Double Click	Configurable double click speed · Configurable double click area
Display Support	display rotation · Support multiple monitors
Division Pattern Settings	Support two halves and four parts with touch function you can also create your own division patterns.
Edge Compensation	Support edge compensation and you can also add your own numbers for it.
Support O.S	All Windows-32 bit O.S ; Windows 7-8-10 XP-64 bit O.S Android ; All Linux ; MAC





### Order information :

AIM-TMOPPCT104-R11 :	【VGA/AUDIO/DVI/USB-TOUCH】	AIM-TMOPPCT104-R12 :	【VGA/AUDIO/DVI/RS232-TOUCH】
Accessory	VGA Cable/AC90~260V Adapter/Power Cable/USB or RS232 Cable/Audio Cable/Cleaning wipes/Driver Disk		
	※DVI Cable(Optional)		



**3 Year Warranty**  
LCD Panel 1 Year





10.4" Embedded Touch Monitor,

AIM-TM0PCT104-R11