




17" inch Embedded Touch Monitor (Projected capacitive Multi-Touch)

Products application :

- POS Terminal
- Industrial PC
- Kiosk
- Gaming
- Medical apparatus
- Personal computer
- Mobile GPS
- Office automation
- Security system of the house
- Car-mounted amusement
- Military equipment
- Communicate



17" inch Embedded Touch Monitor(Projected capacitive Multi-Touch)

Display Specifications :

| | |
|----------------------------|---|
| Active Area | 337 × 270 mm |
| Pixel Pitch | 0.264 × 0.264 mm |
| Brightness | 250 cd/m ² |
| Contrast Ratio | 1000 : 1 |
| Resolution | 1280 x 1024 (SXGA) |
| Viewing Angle | L/R 176° ; U/D 170° |
| Response Time | 5 ms (Tr + Tf) |
| Display Colors | 16.7M |
| Display Modes | 640×480 ; 800×600 ; 1024×768 ; 1280×1024 |
| Signal input | VGA ; Audio ; DVI |
| Mini-Audio out | 1W (8Ω) × 2 |
| OSD Keyboard (Two Options) | ⊙ Menu/Select ⊙ - ⊙ + ⊙ Auto/Exit ⊙ Power |
| Power Source | DC 12V ; ≤15w ; Standby ≤1w |
| Power Consumption | |
| Storage \ Operation | -20~60°C ; 0~50°C |
| VESA | 75×75 or 100×100 mm |
| Casing Colors | Black |
| Casing Size \ Weight | 396.2 × 299 × 50 mm ; 4.2 kg (W×H×D) |
| Carton \ gross weight | 550 × 400 × 180 mm ; 5.7kg (W×H×D) |



※Note 1:R01(OSD Key at the bottom of the Monitor)



※Note 2:R03 (OSD Key on the back of the Monitor)



Touch Feature :

| | |
|--------------|--|
| Input Method | Capacitive stylus, Finger |
| Linearity | ≤2.5mm |
| Surface | ≥7H |
| Life Time | Unlimited |
| Application | Writing and Signature Capture Capability |
| PC Link | USB or RS232(Single-Touch) |

Software Feature :

| | |
|--------------------------------|--|
| Draw Test Controller Languages | Position and linearity verification Support multiple controllers English \ Simple Chinese \ Traditional Chinese \ Japanese \ French \ German \ Spanish \ Korean \ Arabic \ Czech \ Danish \ Dutch \ Greek \ Hungarian \ Italian \ Norwegian \ Russian \ Polish \ Portuguese \ Slovenian \ Swedish \ Thai \ Turkish |
| Mouse Emulator | Right / left button emulation. Auto Right / left Click (PDA function) |
| Touch Style | Drawing a Mode \ button a Mode \ Touch Off/ on Switch |
| Double Click | Configurable double click speed \ Configurable double click area |
| Sound Modes | No sound \ Touch down \ Touch up |
| Display Support | display rotation \ Support multiple monitors |
| Division Pattern Settings: | Support two halves and four parts with touch function, you can also create your own division patterns. |
| Edge compensation | Support edge compensation and you can also add your own numbers for it. |
| Support O.S | All Windows-32 bit O.S Windows7-8-10 : XP-64 bit O.S Android ; All Linux ; MAC |



Order information :

| | | | |
|-----------------------|---|-----------------------|-----------------------------|
| AIM-TMOPPCTU170-R01 : | 【VGA/AUDIO/DVI/USB-TOUCH】 | AIM-TMOPPCTU170-R02 : | 【VGA/AUDIO/DVI/RS232-TOUCH】 |
| AIM-TMOPPCTU170-R03 : | 【VGA/AUDIO/DVI/USB-TOUCH】 | AIM-TMOPPCTU170-R04 : | 【VGA/AUDIO/DVI/RS232-TOUCH】 |
| Accessory | VGA Cable / AC90~260V Adapter / Power Cable / Audio Cable / USB or RS232 Cable /Cleaning wipes / Driver Disk ※DVI Cable(Optional) | | |



