


19" *Projected capacitive Multi-Touch Monitor (Embedded)*

Products application :

- POS Terminal
- Industrial PC
- Kiosk
- Gaming
- Medical apparatus
- Personal computer
- Mobile GPS
- Office automation
- Security system of the house
- Car-mounted amusement
- Military equipment
- Communicate



AIM-RMPCTU190-R31

Order information :

AIM-RMPCTU190-R31

AIM-RMPCTU190-R32


Touch interface :

USB (Multi-Touch*10)

RS232 (Single-Touch)

Mount type :

Embedded (9U Rack Mount)




19" Projected capacitive Multi-Touch Monitor (Embedded)

Display Specifications :

Active Area	376 × 301 mm
Pixel Pitch	0.294 × 0.294 mm
Brightness	250 cd/m ²
Contrast Ratio	1000 : 1
Resolution	1280 x 1024 (SXGA)
Viewing Angle	L/R178° ; U/D170°
Response Time	5ms (Tr + Tf)
Display Colors	16.7M
Display Modes	640×480 ; 800×600 ; 1024×768 ; 1280×1024
Signal input	VGA ; Audio ; Display Port ; HDMI
Speaker	1W (8Ω) × 2
OSD Keyboard	⊙Power ⊙Auto adjust ⊕+ ⊖- ⊙Menu
Power Source	DC 12V (DC Jack Φ2.1mm)
Power Consumption	≤16w
Storage 、 Operation	-20~60°C ; 0~50°C
VESA	75×75 ; 100×100 mm
Casing Colors	Black (OEM other colors)
Casing Size 、 Weight	482 × 399 × 52 mm ; 7 kg (W×H×D)
Carton 、 gross weight	600 × 500 × 200 mm ; 8.5 kg (W×H×D)
Accessory	VGA cable / HDMI cable / Audio cable / AC100~240V Adapter / Power cable / USB or RS232 cable / Cleaning wipes / Driver Disk

※Display Port cable (Optional)

※AiM Touch has the right to update specs without further notice.



19" Projected capacitive Multi-Touch Monitor (Embedded)

Touch Feature :





Input Method	Capacitive stylus, Finger
Linearity	$\leq 2.5\text{mm}$
Surface	$\geq 7H$
Life Time	Unlimited
Application	Writing and Signature Capture Capability

Software Feature :

Draw Test	Position and linearity verification
Controller	Support multiple controllers
Languages	English · Simple Chinese · Traditional Chinese · Japanese · French · German · Spanish · Korean · Arabic · Czech · Danish · Dutch · Greek · Hungarian · Italian · Norwegian · Russian · Polish · Portuguese · Slovenian · Swedish · Thai · Turkish
Mouse Emulator	Right / left button emulation. Auto Right / left Click (PDA function)
Touch Style	Drawing a Mode · button a Mode · Touch Off/ on Switch
Double Click	Configurable double click speed · Configurable double click area
Sound Modes	No sound · Touch down · Touch up
Display Support	display rotation · Support multiple monitors
Division Pattern	Support two halves and four parts with touch function, you can also create
Settings:	your own division patterns.
Edge compensation	Support edge compensation and you can also add your own numbers for it.
Support O.S	All Windows-32/64bit O.S Android ; Linux ; MAC



3 Year Warranty
LCD Panel 1 Year



19" Embedded Touch Monitor.
(9U Rack Mount)

AIM-RMxxxx190-R31
(2025/08/19)