

Note:

Pin 1:Right

Pin 2:Top

Pin 3:Left

Pin 4:Bottom

Pin Pitch:2.54mm

Total Thickness:1.4± 0.1 mm

Surface Hardness:3H

Optical Clarity:80%

Operating Temperature:0°C ~ 50°C

Operating Voltage:DC3 ~ 12V

Resistance:200ohm ~ 900ohm

Linearity:< 1.5%

Faceplate Surface:anti-glare coating

Operation Pressure:35g~60g

Storage Temperature:-20°C ~ 70°C

Message Noise: 5 m sec~15 m sec


Operating Current:5mA ~ 25mA

Isolation Resistance:DC25V 20Mohm UP

Endurance Test: Over 1 million strikes

V.A. : VIEW AREA

A.A. : ACTIVE AREA

瞄準科技有限公司 AIM TOUCH TECHNOLOGY CO.,LTD.	DATE : 2000/09/07	Part Number	ITO Film Type	Glass Type	Glass Thickness	Finished Part Thickness
	MODEL :	AIM-4R-0540-M01-G0N	ANTI GLARE	General	0.7mm	1.0mm±0.1
 WWW.AIMTOUCH.COM	AIM-4R-0540-M01	AIM-4R-0540-M01-G1N	ANTI GLARE	General	1.1mm	1.4mm±0.1
		AIM-4R-0540-M01-G2N	ANTI GLARE	General	1.8mm	2.1mm±0.1

NOTE : All indications are the millimeters.