

Note :

V/A : VIEW AERA

A/A : ACTIVE AERA

Pin 4 : Right

Pin 3 : Left

Pin 2 : Top

Pin 1 : Bottom

Pin Pitch : 2.54 mm

Total Thickness : 1.4 ± 0.1 mm

Surface Hardness : 3H

Optical Clarity : 80%

Operating Temperature : -10°C~60°C

Endurance Test : Over 1 million strikes

Operating Voltage : DC 5~12 V

Resistance : 200Ω~900Ω


Linearity : <1.5%

Faceplate Surface : Anti-glare coating

Operation Pressure : 35g~60g

Storage Temperature : -20°C~70°C

Isolation Resistance : DC25V 20MΩ

瞄準科技有限公司 AIM TOUCH TECHNOLOGY CO.,LTD.	DATE : 2003/09/24	Part Number	ITO Film Type	Glass Type	Glass Thickness	Finished Part Thickness
	MODEL :	AIM-4R-0840-M01-G0N	ANTI GLARE	General	0.7mm	1.0mm±0.1
 WWW.AIMTOUCH.COM.TW	AIM-4R-0840-M01	AIM-4R-0840-M01-G07SN	ANTI GLARE	chemical strengthen	0.7mm	1.0mm±0.1
		AIM-4R-0840-M01-G1N	ANTI GLARE	General	1.1mm	1.4mm±0.1

NOTE : All indications are the millimeters.